

TEST REPORT

244267 / 1

Date received: 27/12/17
Date of test: 09/01/18
Date of issue: 12/01/18

Sample name: PIEDINI SERIE 30 + BASETTA 366 H150.

VOLPATO INDUSTRIE S.P.A.
VIA GALVANI 22/D
31027 SPRESIANO (TV)
ITALIA


Flexural strength at indoor temperature - Catas Procedure

Description of the sample:

Foot diameter: 45 mm
Minimum dimension of the base support: 65 mm
Test condition: 20±5°C

Test equipment:

Instron Dynamometer mod. 5585
Test speed: 10 mm/min



- Test scheme -

Test results:

| Sample n° | Load application point (H) mm | Maximum load N | Maximum moment Nm |
|--------------------|-------------------------------|----------------|-------------------|
| 1 | 145 | 214 | 31 |
| 2 | 145 | 214 | 31 |
| 3 | 145 | 214 | 31 |
| 4 | 145 | 210 | 30 |
| 5 | 145 | 200 | 29 |
| Mean value | | 210 | 30 |
| Standard deviation | | 6 | 1 |

Remarks: All the specimens fail as shown in the photo attached.

Attached: Photo

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

[Signature]
Managing Director
Dr. Andrea Giavon

TEST REPORT

244267 / 1

Date of issue:

12/01/18

Sample name:

PIEDINI SERIE 30 + BASETTA 366 H150.



- Type of failure -

Test report n° 244267

